


Nominal Voltage	12V
Nominal Capacity(20HR)	3.5AH
Dimension	Length 134 1mm (5.28 inches)
	Width 67 1mm (2.64 inches)
	Container Height 60.5 1mm (2.38 inches)
	Total Height (with Terminal) 66.5 1mm (2.62 inches)
Approx Weight Terminal	Approx 1.35 kg (2.98lbs)
Container Material	T1 ABS
Rated Capacity	3.50 AH/0.175A (20hr, 1.80V/cell, 25°C/77°F)
	3.26 AH/0.326A (10hr, 1.80V/cell, 25°C/77°F)
	3.00 AH/0.60A (5hr, 1.75V/cell, 25°C/77°F)
	2.67 AH/0.89A (3hr, 1.75V/cell, 25°C/77°F)
	2.20 AH/2.20A (1hr, 1.60V/cell, 25°C/77°F)
Max. Discharge Current	52.5A (5s)
Internal Resistance	Approx 45mΩ
Operating Temp. Range	Discharge : -15 ~ 50°C (5 ~ 122°F)
	Charge : 0 ~ 40°C (32 ~ 104°F)
	Storage : -15 ~ 40°C (5 ~ 104°F)
Nominal Operating Temp. Range	25 ± 3°C (77 ± 5°F)
Cycle Use	Initial Charging Current less than 1.05A. Voltage 14.4V ~ 15.0V at 25°C (77°F) Temp. Coefficient -30mV/°C
	No limit on Initial Charging Current Voltage 13.5V ~ 13.8V at 25°C (77°F) Temp. Coefficient -20mV/°C
Standby Use	
Capacity affected by Temperature	40° C (104° F) 103%
	25° C (77° F) 100%
	0° C (32° F) 86%
Self Discharge	PowerStar Batteries may be stored for up to 6 months at 25°C (77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.



### Applications

- ◆ All purpose
- ◆ Uninterruptable Power Supply (UPS)
- ◆ Electric Power System (EPS)
- ◆ Emergency backup power supply
- ◆ Emergency light
- ◆ Railway signal
- ◆ Aircraft signal
- ◆ Alarm and security system Electronic apparatus and equipment
- ◆ Communication power supply
- ◆ DC power supply
- ◆ Auto control system



### Constant Current Discharge (Amperes) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	6.67	5.12	4.24	3.67	2.83	2.09	1.76	1.04	0.81	0.66	0.54	0.47	0.378	0.316	0.173
1.80V/cell	8.90	6.54	5.12	4.33	3.34	2.43	1.97	1.14	0.88	0.71	0.58	0.50	0.401	0.326	0.175
1.75V/cell	10.1	7.19	5.6	4.66	3.47	2.52	2.06	1.18	0.89	0.72	0.60	0.52	0.408	0.334	0.177
1.70V/cell	11.1	7.83	5.97	4.9	3.61	2.62	2.13	1.21	0.92	0.74	0.61	0.53	0.413	0.341	0.180
1.65V/cell	12.2	8.45	6.35	5.2	3.81	2.69	2.18	1.23	0.96	0.77	0.63	0.54	0.42	0.348	0.182
1.60V/cell	13.5	9.20	6.79	5.54	4.03	2.80	2.20	1.28	0.99	0.79	0.65	0.55	0.424	0.352	0.183




### Constant Power Discharge (Watts) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	12.2	9.50	7.91	6.91	5.40	4.01	3.40	2.02	1.59	1.29	1.06	0.92	0.746	0.625	0.343
1.80V/cell	16.2	11.9	9.40	8.05	6.28	4.63	3.78	2.19	1.70	1.37	1.13	0.98	0.789	0.643	0.346
1.75V/cell	17.9	12.9	10.2	8.58	6.46	4.76	3.94	2.26	1.72	1.40	1.16	1.01	0.801	0.660	0.349
1.70V/cell	19.1	13.8	10.7	8.90	6.69	4.93	4.05	2.32	1.77	1.44	1.18	1.03	0.811	0.672	0.355
1.65V/cell	20.8	14.7	11.3	9.40	7.00	5.01	4.11	2.34	1.84	1.48	1.21	1.05	0.822	0.685	0.360
1.60V/cell	22.4	15.6	11.9	9.90	7.34	5.19	4.13	2.42	1.88	1.52	1.25	1.07	0.828	0.691	0.361


# Dimensions

## T1 Terminal


Unit: mm [inches]




## Discharge Characteristics




## Float Charging Characteristics




## Temperature Effects in Relation to Battery Capacity




## Effect of Temperature on Long Term Float Life



## Cycle Life in Relation to Depth of Discharge



## Self Discharge Characteristics



- A** No supplementary charge required (Carry out supplementary charge before use if 100% capacity is required.) Supplementary charge required before use. Optional charging way as below: 1. Charged for above 3 days at limited current 0.25CA and constant voltage 2.25V/cell.
- B** 2. Charged for above 20 hours at limited current 0.25CA and constant voltage 2.45V/cell. 3. Charged for 8-10 hours at limited current 0.05CA.
- C** Supplementary charge may often fail to recover the capacity. The battery should never be left standing till this is reached.

## Sales Office

PowerStar sales office:

Add: BatteryJack Inc  
 772 Twin Rail Dr, Minooka, IL 60447  
 Tel: 888-30-POWER  
 Fax: 815-467-7420  
 E-mail: sales@batteryjack.com  
 Http://www.powerstarla.com

