



**METAL
DEFENDER**
AFFORDABLE PROFESSIONAL SECURITY

RoHS **FC** **CE**
COMPLIANT



IMPORTANT! READ BEFORE UNBOXING

Quick start guide for MD-33

Steps:

1. Two (2) people are **required** for the initial setup.
2. Carefully unpack your new walk thru metal detector.
3. After unpacking, you should have the following:

Two (2)	LED Uprights/legs
One (1)	Head Module & Keys
One (1)	Top Rear Support
One (1)	5mm (Hex) Allen key
Eight (8)	Bolts & Nuts
One (1)	Operation Manual

4. On a Flat Clean surface, set the head module on the pad provided.
The head unit should be face down with the LED screens facing the ground. Once the head module is positioned correctly; insert the keys to open and access the motherboard.
5. Attach the Left and Right Uprights/Legs using the Bolts Provided -
DO NOT OVER TIGHTEN

6. Connect the Communication Cables to each Upright and the Main PCB , *make sure they are clipped into place*. Once both of the connectors are **secured** and **fastened** in place, you can close and lock the head module with the keys.
7. Attached the Rear Support Panel with Bolts Provided.
8. Now the unit should be fully assembled & preprogrammed by us ready to go. With one person on each side of the unit, carefully pick it up and stand it upright.
9. Plug your unit into an AC outlet to power on.
(Never plug two metal detectors into the same set of outlets. Each unit must operate on its own set of AC outlets.)
10. Make sure your unit is at least 3-4 feet away from any Metal doors, over ductwork or other metal objects.

**See your Product Manual for Further
details to change security
passwords, fine tune sensitivities etc.**

Product Support:

PH 815-290-5354

PH: 815-467-6464

Fax: 815-467-7420

Email Support@metaldefender