

TEKK

International Incorporated

X-1000^E **EMERGENCY** Series



Up to 5 Watts, 16 Channels
2400 MAh Li-Ion Battery standard
Rugged: Meets Mil-Spec and IP-54
Programmable **EMERGENCY BUTTON**
2-Tone Decode
Inversion Scrambling built in
Remote Stun
Lone Worker Function
HIGHLY water resistant!



EMERGENCY

The multipurpose Tekk X-1000^E
16 Channel portable, with full Mil-Spec
and IP-54 status, is the toughest and highest
specification radio Tekk has ever sold!



Tekk International Incorporated
10601 NW Ambassador Dr G
Kansas City, Mo 64153
Sales@Tekk-Radios.com www.Tekk-Radios.com
800-521-8355 Fax 866-884-3304

Continuing for 2011 . . .
A whole new line-up of
accessories for our own units
as well as for Motorola,
Kenwood, and Vertex . . .

TEKK

International Incorporated

X-1000E Series

EMERGENCY

General Specifications

Standard equipment includes **2400 MAh** Li-Ion battery, Antenna, Rapid Charger and Belt Clip.

Approvals	CE, IC and FCC
Dimensions	4 x 2 x 1.3 inches
Weight	8.5 Oz with 2400 MAh Battery
UHF Frequency range	406 - 475 MHz
VHF Frequency range	136 - 174 MHz
Channels	16 Channels
Nominal voltage	7.4 Volts DC
Channel Spacing	12.5 and 25 KHz programmable



Receiver:	XV-1000E (VHF)	XU-1000E (UHF)
	Sensitivity Selectivity @ 25 KHz Selectivity @ 12.5 KHz Spurious Response Audio Power @ 4% Distortion Channel Spread Battery Drain	12dB SINAD: 0.24 uV Better than: 70dB Better than: 65 dB 70dB 1 Watt @ 16 Ohms 34 Mhz without tuning Stand by: 45mA
Transmitter:	XV-1000E (VHF)	XU-1000E (UHF)
	RF power Hum & Noise @ 25 KHz Hum & Noise @ 12.5 KHz Modulation dist. @ 1 KHz Channel Spread Nominal Battery Drain	5/1 Watt 45 dB 40 dB 4% Max @ 1000 Hz 34 Mhz without tuning 1.5 Amps at 5 Watts

Standard	MIL 810 C		MIL 810 D		MIL 810 E		MIL 810 F	
	Method	Procedure	Method	Procedure	Method	Procedure	Method	Procedure
Low Pressure	500.1	I	500.2	II	500.3	II	500.4	II
High Temperature	501.1	I	501.2	II	501.3	II	501.4	II
Low Temperature	502.1	I	502.2	II	502.3	II	502.4	II
Temperature Shock	503.1	I	503.2	I	503.3	I	503.4	I
Solar Radiation	505.1	I	505.2	I	505.3	I	505.4	I
Rain	506.1	II	506.2	II	506.3	II	506.4	II
Humidity	507.1	II	507.2	III	507.3	III	507.4	-
Salt Fog	509.1	I	509.2	I	509.3	I	509.4	-
Dust	510.1	I	510.2	I	510.3	I	510.4	I
Vibration	514.2	VIII X	514.3	I	514.4	I	514.5	I
Shock	516.2	III V	516.3	IV	516.4	IV	516.5	IV

Environmentals	
Parameter	Specification
Operating Temperature	-30 C to + 60 C
Storage Temperature	-55 C to + 85 C
Humidity	95% RH @ 8 Hr
ESD	IEC 801-2 KV
Water Intrusion	IP 54