

"IT'S NOT A BATTERY, IT'S A BANSHEE"

FEATURE



- High capacity ,Long life
- Sealing structure of PP materials
- High CCA and good starting performance
- maintenance-free design
- Low self-discharge
- C.O.S Application

STZ14ST

SPECIFICATION


Cell per unit	6
Nominal Voltage (V)	12
Nominal Capacity (Ah)	11.2Ah @ 10hour rate F.V(1.75/cell)
Weight	Approx3.57kg(7.86Lbs.)
Polarity:	
Acid Volume:	704 grams
Charge Current :	1.12 Amps
C.C.A.-18℃:	230

DIMENSIONS	Length	Width	Height
Unit: mm	151±1	87±1	110±1
Unit: inch	5.94±0.04	3.43±0.04	4.33±0.04



SELF DISCHARGE AND CAPACITY OF AGM BATTERIES


NOMINAL CAPACITY (%) 20hr RATE



CAPACITY	VOLTAGE
100%	V > 13.0V
90%	12.80 < V < 13.00
80%	12.65 < V < 12.80
70%	12.50 < V < 12.65
60%	12.35 < V < 12.50
50%	12.20 < V < 12.35
40%	12.05 < V < 12.20
30%	11.90 < V < 12.05
20%	11.75 < V < 11.90
10%	11.60 < V < 11.75

DISCHARGE CHARACTERISTICS

Discharge Characteristics



CHARGING METHODS

CHARGING METHODS

Full Charge	Constant-Voltage Charge: Initial charging current: less than 0.3C Voltage:14.40 V ~ 15.00 V at 25℃ (77 ℉) Charging time: 15 ~18h
	Constant-Current Charge: Charging current: 0.1C, when charging voltage up to 14.40V, continue to charge 4h
Floating Charge	No limit on Initial charging current Voltage: 13.50 V ~ 13.80 V at 25℃ (77 ℉)

